



*Leading edge technology in*

# **CAR CARE**

**GASOLINE, DIESEL AND OIL ADDITIVES  
COOLING SYSTEM, AEROSOLS  
GREASES**



### **GASOLINE ADDITIVES**

---

Gasoline Treatment (68217)	1
Gasoline Injector & Carburetor Cleaner (68214)	2

### **DIESEL ADDITIVES**

---

Diesel Treatment (68218)	3
Diesel Injector Cleaner (68212)	4
Diesel Stop Smoke (68226)	5
DPF Regeneration Aid (68220)	6

### **OIL ADDITIVES**

---

Engine Flush (68213)	7
Ceramic Engine Protector (68130)	8
Motor Oil Treatment + MoS2 (68201)	9
Oil Stop Smoke (68114)	10
Oil Stop Leak (68119)	11
Universal Oil Stop Leak (68113)	12

### **COOLING SYSTEM**

---

Radiator Sealer & Conditioner (68215)	13
Radiator Cleaner (68216)	14

### **AEROSOLS**

---

Multi Spray A-40 (68321)	15
Starting Fluid Spray (68332)	16
Rapid Brake & Parts Cleaner (68320)	17

### **AEROSOLS**

---

Carburetor Cleaner Spray (68329)	18
Contact Cleaner Spray (68345)	19
White Grease + PTFE (68323)	20
Silicone Spray (68328)	21
EGR, Turbo & Intake Cleaner (68334)	22
Penetrating Oil + MoS2 (68342)	23
A/C Freshner One Shot (68207)	24
ACL 2000 Adhesive Clear Lube (68331)	25

### **SPECIALTY**

---

Brake Fluid DOT4 (68209)	26
Sili Gasket Pro (68781)	27
Hand Cleaner Pro (68401)	28
Screenwash Concentrate 1:100 (68110)	29
DPF Cleaning Kit (68231)	30
Fuel System Purge (68222)	31
Brake Paste Anti-Squeal (68400)	32

### **GREASE**

---

Lithium Complex Grease 2 (68770 & 68773)	33
Lithium Grease MP2 (68771)	34
Lithium Moly EP2 Grease (68772)	35

### **PREMIUM SERIES**

---

Gasoline Detox PRO (68777)	36
Diesel Detox PRO (68778)	37
BORTEC Friction Fighter (68776)	38

## GASOLINE TREATMENT

### BENEFITS

- ✓ Cleans the fuel system including valves and injectors
- ✓ Restores power and performance
- ✓ Eliminates rough idling and engine hesitation
- ✓ Improves combustion
- ✓ Reduces gasoline consumption
- ✓ Prevents fuel system corrosion
- ✓ Reduces emission of hazardous exhaust gas

### USAGE

All gasoline (leaded or unleaded) engines with injectors or carburetor. Will not harm catalytic converters.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with gasoline. One bottle treats 40 to 60 litres of gasoline.

### DOSAGE

Normal use: one bottle every 2000 km.  
Intensive or sportive use: one bottle for each tank filling.

### GASOLINE

#### Packaging Details

Art. No.:	68217
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,80
Flash Point:	> 61°C
Colour:	Clear
Odour:	Characteristic



## GASOLINE INJECTOR & CARBURETOR CLEANER

### BENEFITS

- ✓ Cleans injectors, carburetors and the entire gasoline supply system
- ✓ Restores power and performance
- ✓ Prevents deposits of gums, varnish and sludge
- ✓ Eliminates valve sticking
- ✓ Eliminates rough idling, hesitation or knocking
- ✓ Reduces gasoline consumption and protects against corrosion
- ✓ Reduces emission of hazardous exhaust gas
- ✓ Improves combustion and driveability

### USAGE

All gasoline (leaded or unleaded) engines with injectors or carburetor. Will not harm catalytic converters.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with gasoline. One bottle treats 40 to 60 litres of gasoline.

### DOSAGE

Normal use: one bottle every 2000 km.  
Intensive or sportive use: one bottle for each tank filling.

### GASOLINE

#### Packaging Details

Art. No.:	68214
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,80
Flash Point:	> 61°C
Colour:	Clear
Odour:	Characteristic



## DIESEL TREATMENT

### BENEFITS

- ✓ Cleans the entire fuel system including injectors
- ✓ Increases cetane number
- ✓ Restores power and performance
- ✓ Improves combustion and reduces fuel consumption
- ✓ Protects the fuel system against corrosion
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Lubricates the diesel fuel pump in case of low sulphur fuel

### USAGE

For all diesel engines (incl. common rail) with or without turbochargers running on low or normal sulphur level diesel fuel.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel. One bottle treats 40 to 60 litres of diesel fuel.

### DOSAGE

Normal use: one bottle every 2000 km.  
Intensive or sportive use: one bottle for each tank filling.

### DIESEL

#### Packaging Details

Art. No.:	68218
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,81
Flashpoint:	> 61°C
Colour:	Clear / Amber
Odour:	Characteristic



## DIESEL INJECTOR CLEANER

### BENEFITS

- ✓ Removes carbon deposits from injectors and prevents needles from seizing
- ✓ Reduces corrosion and wear
- ✓ Improves combustion with effective cleaning agents and a strong cetane improver
- ✓ Decreases operational cost by lowering fuel consumption and maintenance costs
- ✓ Reduces engine noise
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Improves starting performance and eliminates knocking under partial loads
- ✓ Contains a highly effective lubricity agent to lubricate the fuel pump

### USAGE

For all diesel engines (incl. common rail) with or without turbochargers running on low or normal sulphur level diesel fuels.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel. One bottle treats 40 to 60 litres of diesel fuel.

### DOSAGE

Normal use: one bottle every 2000 km.  
Intensive or sportive use: one bottle for each tank filling.

### DIESEL

#### Packaging Details

Art. No.:	68212
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,81
Flashpoint:	> 61°C
Colour:	Clear / Amber
Odour:	Characteristic



## DIESEL STOP SMOKE

### BENEFITS

- ✓ Reduces smoke and emission of hazardous exhaust gases from diesel engines
- ✓ Optimizes fuel combustion
- ✓ Cleans the fuel system and protects it from corrosion

### USAGE

For all diesel engines (incl. common rail) with or without turbochargers running on low or normal sulphur level diesel fuels.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel.

### DOSAGE

One bottle treats 40 to 60 litres of diesel fuel. Use one bottle every 2.000 km.

## DPF REGENERATION AID

### BENEFITS

- ✓ Ensures complete and rapid diesel particulate filter regeneration
- ✓ Reduces ignition temperature of trapped soot ensuring extraordinary combustion at temperatures typically encountered during normal engine operation
- ✓ Prevents performance loss caused by clogged diesel particulate filters
- ✓ Reduces particulate emission assisting in meeting strict legislation and emission limits
- ✓ Extends lifetime of the expensive diesel particulate filter
- ✓ Most economic way of soot reduction without any changes to the fuel system
- ✓ Regeneration of diesel particulate filters is 5-10 times faster and more complete than when using a catalyst coated diesel particulate filter
- ✓ No secondary emissions
- ✓ Can be used for all diesel engines with standard or retrofitted diesel particulate filter

### USAGE

For all diesel engines (incl. common rail and turbo charged engines) with standard or retrofitted diesel particulate filter.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel.

### DOSAGE

Use one bottle on regular basis. One bottle treats 40 - 60 liters of diesel. Do not overdose.

### DIESEL

#### Packaging Details

Art. No.:	68226
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,81
Flashpoint:	> 61°C
Colour:	Clear / Amber
Odour:	Characteristic



### DIESEL

#### Packaging Details

Art. No.:	68220
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,78
Flashpoint:	> 61°C
Colour:	Amber / Brown
Odour:	Characteristic



## ENGINE FLUSH

### BENEFITS

- ✓ Internally cleans and flushes the engine with highly effective cleaning agents
- ✓ Eliminates gums, varnish and sludge
- ✓ Easily removes contaminants like carbon deposits, soot and liquids (water and fuel rests) from the engine
- ✓ Reduces fuel consumption and exhaust emissions by restoring engine condition and enabling the fresh oil to perform optimally
- ✓ Contains no harmful solvents

### USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Compatible with all mineral, semi synthetic or full synthetic motor oils.

### INSTRUCTIONS

1. Before changing oil, pour the contents of one bottle in the crank case of the warm engine.
2. Let the engine run for 15 minutes, alternatively at low and high rpm.
3. Drain the oil from the crank case.
4. Replace oil filter.
5. Refill crank case with recommended fresh motor oil.

### DOSAGE

One bottle treats a crankcase of 3 to 6 litres.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68213
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,87
Flashpoint:	> 200°C
Colour:	Clear / Amber
Odour:	Characteristic



## CERAMIC ENGINE PROTECTOR

### BENEFITS

- ✓ Significantly reduces friction and wear
- ✓ Reduces fuel and oil consumption
- ✓ Restores engine power
- ✓ Provides long term protection of your engine
- ✓ Improves load carrying capacity of the lube film
- ✓ Reduces emission of hazardous exhaust gases

### USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Not suitable for motorcycles using a wet clutch.

### DIRECTION

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Drive approximately 15 minutes to obtain optimum result. Make sure the oil contents do not exceed the maximum oil level in your engine.

### DOSAGE

One bottle treats 4 to 6 litres of motor oil. Due to its outstanding bonding to metal, this advanced product retains its properties and effectiveness even after oil change. Recommended use: every 50.000 km.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68130
Contents:	450 ml
Packaging:	12x450 ml
Pallet:	70 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,90
Flash Point:	> 200°C
Viscosity @ 20°C:	~ 720 mPa.s
Colour:	Cream / White



## MOTOR OIL TREATMENT + MoS2

### BENEFITS

- ✓ Significantly reduces friction and wear by forming a high load-bearing lubricating MoS2 film on all friction and sliding surfaces inside the engine
- ✓ Reduces fuel and oil consumption and lowers toxic emissions
- ✓ Improves viscosity of the oil and restores engine power
- ✓ Sub-micron sized MoS2 particles guarantee lubrication during cold starts and in case of emergencies
- ✓ Selected additives guarantee lower friction, effective long term protection of your engine and optimal performance

### USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters.

### DIRECTION

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Make sure the oil contents do not exceed the maximum oil level in your engine.

### DOSAGE

One bottle treats 3 to 5 litres of motor oil. Use one bottle just after every oil change.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68201
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	70 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,89
Flash Point:	> 175°C
Colour:	Blackish
Odour:	Characteristic



## OIL STOP SMOKE

### BENEFITS

- ✓ Improves viscosity of the oil
- ✓ Ensures a strong protective oil film
- ✓ Improves engine performance by enhancing motor compression
- ✓ Stops oil leakage through seals and regain all-new pliability
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Does not contain harmful solvents

### USAGE

Oil stop smoke can be used in all mineral, synthetic, single or multi-grade oils and is not harmful for catalytic converters.

### DIRECTION

Add the contents of one bottle to the warm oil. Allow the product to fully drain from the can. Let the engine run or drive for 15 minutes to obtain a good mixture of the product. Make sure the oil contents do not exceed the maximum oil level.

### DOSAGE

One bottle treats 3 to 5 litres of motor oil. Use when required.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68114
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	70 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,87
Flash Point:	> 175°C
Viscosity @ 100°C:	340 cSt
Colour:	Amber
Odour:	Characteristic



## OIL STOP LEAK

### BENEFITS

- ✓ Stops and prevents oil leakages through seals
- ✓ Reduces oil consumption
- ✓ Makes seals swell back to original size and regain all-new pliability
- ✓ Eliminates the need for expensive engine repair
- ✓ Prolongs the service life of the engine
- ✓ Improves the viscosity of the motor oil
- ✓ Improves engine performance by enhancing motor compression
- ✓ Prevents or reduces emission of blue exhaust smoke
- ✓ Reduces engine noise
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Does not contain harmful solvents or solids

### USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters.

### DIRECTION

Add contents of one bottle to the warm motor oil. Make sure the oil contents do not exceed the maximum oil level in your engine.

### DOSAGE

One bottle treats a crankcase of 4 to 6 litres.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68119
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	70 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,88
Colour:	Golden / Brown
Odour:	Characteristic



## UNIVERSAL OIL STOP LEAK

### BENEFITS

- ✓ Allround additive, works in engine & gear oil, ATF, power steering fluid and hydraulic oils
- ✓ Stops and prevents oil leakages through seals like valves, crankshafts, dusts, oil filter O-rings, oil pans and all other plastic or rubber based seals
- ✓ Reduces oil consumption
- ✓ Makes seals swell back to original size and regain all-new pliability
- ✓ Eliminates the need for expensive repairs
- ✓ Prolongs the service life of the engine
- ✓ Improves engine performance by enhancing motor compression
- ✓ Prevents or reduces emission of blue exhaust smoke
- ✓ Reduces engine noise
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Does not contain harmful solvents or solids

### USAGE

Universal Oil Stop Leak can be used in all oils to stop leakage. Does not clog filters and is not harmful for catalytic converters. DO NOT ADD TO BRAKE FLUID.

### DIRECTION

Determine total oil volume in the system to be treated. Add Universal Oil Stop Leak in a volume equal to 1% of the total. Add preferably to warm oil. Operate the system for 10 minutes.

### OIL ADDITIVES

#### Packaging Details

Art. No.:	68113
Contents:	50 ml
Packaging:	24x50 ml
Pallet:	100 cartons
Languages:	EN, DE

#### Technical Specifications

Density g/cm <sup>3</sup> :	1,03
Colour:	Amber
Odour:	Characteristics





## RADIATOR SEALER & CONDITIONER

### BENEFITS

- ✓ Permanently and reliably seals and prevents within seconds hair cracks and leakages up to 0.9 mm in the radiator, the heater radiator, the water pump, the cylinder head gasket and the engine block
- ✓ Eliminates the need for expensive repair
- ✓ Lubricates the water pump and does not contain acids and is not poisonous
- ✓ Does not harm rubber hoses, metal parts and gaskets

### USAGE

Suitable for all aluminium, plastic and steel radiators of cooling systems in petrol, diesel and LPG engines. Compatible with water, cooling fluids and conventional anti freeze.

### DIRECTION

Shake well before use. Add the contents of the can to the cooling system with switched on heating and warm (not hot) running engine. Keep engine running for approximately 10 minutes or drive a short distance. Be careful when opening the radiator / cooling system: hot coolant or steam might escape from the system. Dirty cooling systems should first be cleaned with ARDINA Radiator Cleaner.

### DOSAGE

The content of one bottle is sufficient for cooling systems with a volume of up to 12 litres.

### COOLING SYSTEM

#### Packaging Details

Art. No.:	68215
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	1,02
PH-value:	7,0
Colour:	Brownish
Odour:	Characteristics



## RADIATOR CLEANER

### BENEFITS

- ✓ Effectively cleans the entire cooling system and removes sludge, rust, scale and other deposits
- ✓ Improves the heat transfer from engine to cooling system and prevents overheating
- ✓ Prevents build up of acids and contaminants
- ✓ Does not contain acids and is not poisonous
- ✓ Does not harm rubber hoses, metal parts and gaskets

### USAGE

Suitable for all aluminium, plastic and steel radiators of cooling systems in petrol, diesel and LPG engines. Compatible with water, cooling fluids and conventional anti freeze.

### DIRECTION

Shake well before use. Add contents of one bottle to the radiator, drive for about 30 minutes and drain cooling system. Flush with water and refill cooling system. Be careful when opening or draining the radiator / cooling system: hot coolant or steam might escape from the system.

### DOSAGE

The content of one bottle is sufficient for cooling systems with a volume of up to 12 litres.

### COOLING SYSTEM

#### Packaging Details

Art. No.:	68216
Contents:	250 ml
Packaging:	24x250 ml
Pallet:	50 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	1,00
PH-Value:	10,0
Colour:	Colourless
Odour:	Characteristic



## MULTI SPRAY A-40

### BENEFITS

- ✓ Rapidly loosens locked, rusted or corroded parts with its effective penetrating power
- ✓ Effectively cleans parts from dirt, grime and grease
- ✓ Lubricates treated parts
- ✓ Removes humidity from locks, ignitions and treated parts
- ✓ Protects against rust and corrosion
- ✓ Resistant to hot, cold and salt water
- ✓ Does not affect rubber, plastics or paint

### USAGE

In workshops, cars, caravans, motorcycles, bicycles, home applications, tools, etc.

### DIRECTION

Shake well before use. Spray on the parts to be treated. For loosening parts and removing humidity: allow to set a few minutes. If parts remain locked, repeat the operation.

### DOSAGE

To be used whenever required.

## STARTING FLUID SPRAY

### BENEFITS

- ✓ Enables quick starting of petrol and diesel engines
- ✓ Especially effective with cold starts during cold or wet seasons
- ✓ Prevents carburetors from freezing
- ✓ Applies easily

### USAGE

In cars, trucks, agriculture and industry applications.

### DIRECTION

Shake well before use. For petrol engines: spray into the carburetor or vacuum hose. For diesel engines: spray into the air inlet. Spray moderately to avoid excessive fluid and uncontrolled running of the engine.

### DOSAGE

To be used whenever required.

## AEROSOLS

### Packaging Details

Art. No.:	68321
Contents:	400 ml
Packaging:	12x400 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

### Technical Specifications

Density g/cm <sup>3</sup> :	0,83
Colour:	Colourless
Odour:	Vanilla



## AEROSOLS

### Packaging Details

Art. No.:	68332
Content:	250 ml
Packaging:	12x250 ml
Pallet:	98 cartons
Language:	EN, DE, FR, ES

### Technical Specifications

Density g/cm <sup>3</sup> :	0,61
Colour:	Clear / Colourless
Odour:	Characteristic



## RAPID BRAKE & PARTS CLEANER

### BENEFITS

- ✓ Effectively removes contaminants like oil, grease, salts, brake fluid and street grime from all possible parts
- ✓ Prevents brake squeaking
- ✓ Special detergents dissolve even crusted, corroded and hardened dirt
- ✓ Dries quick, precise and secure leaving absolutely no residue

### USAGE

High active cleaner with intensive cleaning power for brake parts, couplings, gear boxes, engine components, etc. Pre-treatment for surfaces which are to be glued, screwed or coated. Excellent cleansing and dirt removal qualities for glass, ceramics and stone. The ideal cleanser for industry and workshop applications while repairing and assembling.

### DIRECTION

Shake well before use. Spray on the parts to be treated allowing the agent to dissolve, respectively evaporate.

### DOSAGE

To be used when ever required.

### AEROSOLS

#### Packaging Details

Art. No.:	68335
Contents:	600 ml
Packaging:	12x600 ml
Pallet:	60 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,70
Colour:	Clear / Colourless
Odour:	Petroleum like



## CARBURETOR CLEANER SPRAY

### BENEFITS

- ✓ Removes oil, grease and fuel residues quickly and effectively from the carburetor intake
- ✓ Cleans and degreases butterfly throttle valves as well as the internal and external parts of the idle speed actuators and carburetor
- ✓ Lubricates all previously cleaned moving parts
- ✓ Dries quick, precise and secure leaving absolutely no residue

### USAGE

Specially formulated blend of cleansing and lubricating agents ideal in industry and workshop applications for repairs, assembly and routine maintenance.

### DIRECTION

Shake well before use. Spray parts to be treated intensely from a distance of approx. 20 cm allowing the agent to dissolve, respectively evaporate. Air dry the parts.

### DOSAGE

To be used whenever required. Repeat the treatment several times if deemed necessary.

### AEROSOLS

#### Packaging Details

Art. No.:	68329
Contents:	500 ml
Packaging:	12x500 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,74
Colour:	Clear / Colourless
Odour:	Characteristics



## CONTACT CLEANER (NON-CONDUCTIVE)

### BENEFITS

- ✓ Penetrates, lubricates, cleans and protects
- ✓ Effectively cleans and degreases dust, carbon, oxide deposits and other common contaminants
- ✓ Is non-conductive and easily removes oil, grease and dirt
- ✓ Provides long lasting protection of all types of metal, repels damp
- ✓ Special additives prevent corrosion
- ✓ Dries quickly, precise and secure leaving absolutely no residue

### USAGE

Highly active cleaner and degreaser for spark plugs, electrical motors, contractors, relays, carbon brushes, battery terminals, switchgears, and all other electrical items. Can be safely applied to plastic, rubber and metal surfaces.

### DIRECTION

Shake well before use. Spray sufficiently onto the parts to be treated, i.e. electrical wiring, spark plugs and distributor cap, allowing the agent to dissolve, respectively evaporate.

### DOSIS

To be used whenever required.

## AEROSOLS

### Packaging Details

Art. No.:	68345
Contents:	200 ml
Packaging:	12x200 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

### Technical Specifications

Density g/cm <sup>3</sup> :	0,68
Ignition Temp:	236°C
Colour:	Clear / Colourless
Odour:	Characteristics



## WHITE GREASE + PTFE

### BENEFITS

- ✓ Universally applicable non dripping and non hardening grease for lubrication of all moving metal parts
- ✓ Protects against corrosion and has excellent long term lubricating properties, even under severe conditions, due to its PTFE content
- ✓ Water and heat resistant
- ✓ Protects even in wet, saline, acidic and alkaline environments

### USAGE

For lubrication and protection of chains, axles, bearings, springs, locks, hinges and other metal to metal contacts operating under severe conditions with extreme pressures, severe impacts and vibrations.

### DIRECTION

Shake well before use. Spray on the parts to be treated. Spraying distance: 20-30 cm.

### DOSAGE

To be used whenever required.

## AEROSOLS

### Packaging Details

Art. No.:	68323
Contents:	400 ml
Packaging:	12x400 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

### Technical Specifications

Density g/cm <sup>3</sup> :	0,69
Temp. Range:	-20°C – +150°C
NLGI:	2
Drop Point:	180°C
Welding Load:	> 300 kg
Colour:	White



## SILICONE SPRAY

### BENEFITS

- ✓ Protects and conditions with excellent lubricating qualities plastic, rubber and metal parts
- ✓ Leaves a clean, grease free, non-hardening lubricating film
- ✓ Makes jammed and squeaking parts run well again, sunroofs and seat rails slide freely
- ✓ Rubber parts are reconditioned, does not embrittle, freeze or adhere to other objects
- ✓ Protects against oxidation and corrosion, plastic parts regain a fresh gleam
- ✓ Excellent surface adherence
- ✓ Excellent high temperature resistance
- ✓ Water-repellent, protects and isolates electric contacts from moisture

### USAGE

Protection, lubrication, parting and conditioning agent for plastic, rubber and metal parts.

### DIRECTION

Shake well before use. Spray from a distance of 20 - 30 cm onto the cleaned and degreased surfaces to be treated. Rub surfaces with a clean, soft cloth.

### DOSAGE

To be used whenever required.

## AEROSOLS

### Packaging Detail

Art. No.:	68328
Contents:	500 ml
Packaging:	12x500 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

### Technical Specifications

Density g/cm <sup>3</sup> :	0,58
Colour:	Colourless / Clear
Odour:	Characteristic



## EGR, TURBO & INTAKE CLEANER

### BENEFITS

- ✓ Effectively cleans the Turbo, EGR system, intake, throttle valve and combustion chamber from power robbing deposits and lacquer-like compounds
- ✓ Improves engine performance, fuel economy, engine idling and starting
- ✓ Increase lifetime of sensitive engine components like catalysts and diesel particulate filters
- ✓ Reduces harmful emissions

### USAGE

For all gasoline and diesel engines with or without turbochargers.

### DIRECTION

Follow the instructions carefully or have an automotive repair shop carry out this treatment.

### DOSAGE

The content of one aerosol is sufficient for two treatments via the air intake or cleaning dismantled parts as per your requirements. ETI should be used regularly on engines sensitive to intake fouling and DPF saturation.

To prevent carbon deposit build up regular use of ARDINA fuel treatments is highly recommended.

## PRO-LINE

### Packaging Details

Art. No.:	68334
Contenido:	400 ml
Embalaje:	12x400 ml
Pallet:	98 cartons
Languages:	EN, ES, FR, IT

### Technical Specifications

Density g/cm <sup>3</sup> :	0,82
Flash Point:	-97
Boiling Point:	-44
Colour:	White / Foam



## PENETRATING OIL + MoS2

### BENEFITS

- ✓ Disperses rust, scale and other oxides
- ✓ Penetrates into hard-to-reach areas quickly
- ✓ Frees metal parts seized by dirt, rust, corrosion or dried-up greasy deposits
- ✓ Eases quick disassembly of mechanical components, fittings, assemblies, nuts and bolts and other close tolerance fasteners
- ✓ Leaves a solid lubricating MoS2 film
- ✓ Functions as an anti-seize product facilitating future disassembly

### USAGE

In workshops, cars, caravans, motorcycles, bicycles, home applications, tools, etc.

### DIRECTION

Shake well before use. Spray on the parts to be treated. For loosening parts and removing humidity: allow to set a few minutes. If parts remain locked, repeat the operation.

### DOSAGE

To be used whenever required.

## A/C FRESHNER ONE SHOT

### BENEFITS

- ✓ Easy to use
- ✓ Deodorises and prevents the formation of unpleasant odours

### USAGE

A/C Freshner can be used in all cars with air conditioning and air circulation systems.

### DIRECTION

The aerosol should be at room temperature. Shake well before use. Start the engine and let the engine idle. Put both seats and the back of the seats in front position. Switch the a/c system on full power in the recirculation position. Place the A/C Freshner behind the seats, activate the aerosol by pressing the nozzle once and close the door. Do not place face above the spray. After full evaporation of the A/C Freshner, the engine should idle for 5 minutes. Turn off the engine, open the doors and let it ventilate for at least 10 minutes.

**IMPORTANT: DO NOT SMOKE OR KEEP OPEN FIRE ROUND THE VEHICLE DURING AND AFTER EMPTYING THE AEROSOL, THERE IS A RISK OF EXPLOSION UNTIL THE CAR IS WELL VENTILATED.**

### DOSAGE

One-shot.

## AEROSOLS

### Packaging Details

Art. No.:	68342
Content:	400 ml
Packaging:	12x400 ml

### Technical Specifications

Density g/cm <sup>3</sup> :	0,70
Colour:	Yellowish
Odour:	Petroleum-like



## AEROSOLS

### Packaging Details

Art. No.:	68207
Contents:	150 ml
Packaging:	12x150 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

### Technical Specifications

Density /cm <sup>3</sup> :	0,65
Colour:	Colourless
Odour:	Apple



## ADHESIVE CLEAR LUBE ACL2000

### BENEFITS

- ✓ A versatile, adhesive, high pressure resistant synthetic lubricant
- ✓ Excellent penetrating properties
- ✓ Provides excellent lubrication and leaves an extremely resistant lubricant film reducing noise and vibration
- ✓ Protects against wear and corrosion
- ✓ Wide operating temperature range (-35°C to 200°C)
- ✓ Does not affect rubber, plastics or paint
- ✓ Resistant to water, salt, alkaline and weak acids

### USAGE

All applications where parts are subject to high pressure, speed, impact and vibration and where a strong, adhesive and durable lubricant film is required, e.g. chains, hinges, shift, clutch and throttle linkages, Bowden cables, drag link ends, levers, racks and pinions, open gears and many more.

### DIRECTION

Spray on the parts to be treated. After application the solvent evaporates leaving a highly adhesive, durable and waterproof lubricant.

### DOSAGE

To be used whenever required.

## AEROSOLS

### Packaging Details

Art. No.:	68331
Content:	400 ml
Packaging:	12x400 ml

### Technical Specifications

Density g/cm <sup>3</sup> :	0,68
Colour:	Clear / Colourless
Odour:	Characteristic



## BRAKE FLUID DOT4

### DESCRIPTION

ARDINA Brake Fluid DOT 4 is a high performance brake and clutch fluid with a minimum dry boiling point of 250 °C. Greatly exceeds SAE J1703 / J1704, FMVSS Nr.116 DOT 3 / DOT 4 and ISO 4925 specifications. Its high boiling point increases durability and safety. Provides excellent corrosion protection and rubber seal compatibility.

### USAGE

Suitable for all hydraulic brake and clutch systems requiring synthetic fluid of DOT 4 specifications.

### DIRECTION

Follow vehicle manufacturer's instructions when adding or replacing brake fluid. Miscible with all other brake fluids of DOT 4 specification. Must not be mixed with silicone type or silicone ester type of brake fluids. Store brake fluid clean and dry. Avoid contamination with fluids of any other kind and do not refill the container. Store brake fluid in the original container only. Keep the container tightly closed to prevent the absorption of moisture. Do not spill on car lacquer.

### DOSAGE

Follow the service interval recommended by the car manufacturer. If no recommendation is given, it is advised to replace brake fluid at least every two years, preferably every year, every 40.000 km or when the percentage of water in the brake fluid is more than 2%.

## SPECIALTY

### Technical Specifications

Properties	Unit	DOT 4 Specs	Typical Value
Appearance	-	-	Clear Liquid
Colour	-	-	Light Amber
Density @ 20°C	g/ml	-	1.06
Water content %	% (m/m)	-	max 0.20
Equilibrium Reflux Boiling Point (ERBP)	°C	≥ 230	260
Wet Equilibrium Reflux Boiling Point (WERBP)	°C	≥ 155	160
Kinematic viscosity @ -40 °C	mm <sup>2</sup> /s	≤ 1800	1400
@ 100 °C	mm <sup>2</sup> /s	≥ 1.5	2.2



## SILI GASKET PRO

### DESCRIPTION

Ardina Sili Gasket Pro is a low volatile automotive sealant, supplied as a paste like, one component material. Sili Gasket Pro has been specifically formulated to resist slumping and sagging even when applied to vertical and horizontal surfaces overhead.

### BENEFITS

- ✓ Formulated for high temperatures (up to 300°C) and / or heavy duty applications.
- ✓ Ideal also for application in areas with low temperatures (down to -40°C).
- ✓ Replaces almost any cut gasket by making reliable "formed-in-place" gaskets that resist cracking, shrinking and migrating caused by thermal cycling.

### DESCRIPCIÓN

Sili Gasket Pro can be used for sealing turbo housings, exhaust manifolds and oxygen sensors. Fixing automotive and appliance trim including: metal, fabric and fabric backed plastics. For sealing trailers, trucks, cabs, bonding and sealing appliance parts. Not recommended for use on PE, PP, PC, PMMA, PTFE, soft plastics, neoprene or bituminous substrates.

### DIRECTION

All surfaces must be clean, dry and dust free. All loose flaking surface coatings and old sealant should be removed by scraping, abrading or other suitable means prior to application. Glass and metal surfaces should be cleaned with appropriate solvent based cleaner prior to application to ensure optimum adhesion. Apply the product evenly to the surface. Smooth the product down after application using a spatula (or similar) wetted with water.

### DOSAGE/STORAGE

Use the amount of which fits the treatment. Store in a cool dry area between 5°C and 40°C out of direct sunlight and protect from frost. This product has a shelf life of approximately 15 months.

### SPECIALTY

#### Packaging Details

Art. No.:	68781
Content:	200 ml
Packaging:	12x200 ml
Pallet:	84 cartons
Languages:	EN, ES, IT, FR, DE, RU

#### Technical Specifications

Colour:	Black
Application Temperature:	+5°C till +40°
Base:	Acetoxy
Density:	1,03 g/ml
Elongation at Break:	400%
Shore-A hardness:	29 Shore A
Skin Formation@23°C/50%RH:	5 - 6 min
Temperature Resistance:	-40°C till +300°C



## HAND CLEANER YELLOW

### USAGE

Extremely powerful hand cleaner for the removal of heavy industrial soils. Very effective cleaning thanks to natural ingredients and grain that does not damage the skin. Especially suitable for the elimination of stubborn dirt such as paint, ink, glue and tar. Excellent skin care. Fresh lemon fragrance of natural ingredients.

### DIRECTION

Apply a small amount of hand cleaner to dry hands, rub it well enough until it is thoroughly mixed with the dirt. After that, rinse with water or wipe with a cloth. Dry your hands thoroughly. Close the container tightly and store in a cool, dry place free from frost.

### pH

1 2 3 4 5 6 7 8 9 10 11 12 13 1 4

### SPECIALTY

#### Packaging Details

Art. No.:	68401
Content:	4,5 ltr
Packaging:	4x4,5 ltr
Pallet:	32
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,94
PH-Value:	9
Colour:	Yellow
Odour:	Fresh Lemon





## SCREENWASH CONCENTRATE 1:100

### BENEFITS

- ✓ Highly concentrated effective windscreen cleaner
- ✓ Removes dirt, water spots and insects
- ✓ Leaves a pleasant smell and a streak free finish

### USAGE

ARDINA Screenwash Concentrate is a highly concentrated product which allows a mixing ratio of 1:100.

### DIRECTION

Pour the contents of one bottle (32 ml) in the screenwash fluid reservoir and add 3 litres of water.

### DOSIS

To be used whenever required.

### SPECIALTY

#### Packaging Details

Art. No.:	68110
Content:	32 ml
Packaging:	100x32 ml

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,99
Flash Point:	40°C
PH Value:	6,3
Boiling Point:	> 85°C
Colour:	Red / Orange
Odour:	Peach



## DIESEL PARTICULATE FILTER (DPF) CLEANING KIT

### PRODUCT DESCRIPTION

The ARDINA DPF Cleaning kit is a cost / time-effective and sustainable cleaning method for clogged DPF's.

The kit consists of three different steps, two of which are applied via a special cleaning gun. These fluids loosens, disperse and flush out soot, which will facilitate a full regeneration of the filter. The third step is a fuel additive (ARDINA DPF Regeneration Aid) which prevents future problems.

### BENEFITS

- ✓ Loosen soot deposits in the diesel particulate filter
- ✓ Facilitates complete regeneration
- ✓ Easy and quick to use
- ✓ Prevents expensive replacement
- ✓ Prevents repeated problems

### USAGE / DIRECTION / DOSAGE

Clean when required. Please refer to the product manual.



### PRO-LINE

#### Packaging Details

Art. No.:	68231
Packaging:	4 x kit
Pallet:	30 cartons
Languages:	EN

## FUEL SYSTEM PURGE

### BENEFITS

Cleans injectors, valves, valve stems, piston, piston rings and the combustion chamber without the need for disassembly.

- ✓ Restores injection spray pattern and injection time
- ✓ Frees and prevents sticking exhaust valves
- ✓ Eliminates rough idling, engine hesitation and improves starting
- ✓ Reduces gasoline consumption and emission of hazardous exhaust gases
- ✓ Restores power and performance and optimizes engine operation

### USAGE

All gasoline (leaded or unleaded) engines with injectors (including direct injection engines) or carburettor. Will not harm catalytic converters.

### DIRECTION

- Product is ready-to-use and does not need to be mixed with gasoline.
- Use maximum one bottle (1L) for full and optimized cleaning.
- To be used only with professional equipment suitable for direct fuel supply to the engine.
- Make sure the engine is at normal operating temperature when applying this product.
- DO NOT ADD TO THE FUEL TANK.

### DOSAGE

Recommended treatment every 25.000 km or when problems like poor running or starting, rough idling or excessive exhaust emissions occur.

### PRO-LINE

#### Packaging Details

Art. No.:	68222
Content:	1 ltr
Packaging:	12x1 ltr
Pallet:	50 cartons
Languages:	EN

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,74
Colour:	Clear / Amber
Odour:	Characteristic
Flash Point:	< 0°C
Boiling Point:	>35°C



## BRAKE PASTE ANTI-SQUEAL

### PRODUCT DESCRIPTION

ARDINA Brake Paste (anti-squeal) is a premium quality anti-squeal and anti-seize paste containing a soft aluminum solid lubricant. Formulated to be used in extreme environment.

### BENEFITS

- ✓ Lubricates and separates under extreme pressure loads and temperatures (-40°C to >1.100°C)
- ✓ Quiets, eliminates and prevents high-pitched braking squeal
- ✓ Hinders weld seals, seizures and corrosion
- ✓ Reduces the effect of acids and chemicals
- ✓ Resistant to fresh and salt water

### USAGE

Apply sparingly to clean component surfaces. Ensure surfaces are completely coated before assembly.

### DOSAGE

To be used whenever required.



### SPECIALTY

#### Packaging Details

Art. No.:	68400
Content:	5,5 gr
Packaging:	100x5,5 gr
Pallet:	24 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Colour:	Aluminum grey
Odour:	Characteristic

## LITHIUM COMPLEX GREASE 2

### PRODUCT DESCRIPTION

ARDINA Lithium Complex Grease 2 Red is a specially developed multi-purpose lithium complex grease for the lubrication of all plain and anti-friction bearings for use in automotive and industrial applications. The lithium complex grease shows remarkable performance and provides continued lubrication intervals over a wide operating temperature range.

### BENIFITS

- ✓ Highly versatile
- ✓ Good oxidation stability provides lasting lubrication at high temperatures >150°C
- ✓ Excellent extreme pressure (resistant to weld loads >450 kg) and anti-wear performance
- ✓ Exceptional mechanical stability extends relubrication intervals
- ✓ Good water resistance protects components from corrosion operating in wet conditions
- ✓ No adverse effect on sealings

### USAGE

Follow the recommendations from the equipment and / or bearing manufacturer. Check compatibility with the grease applied previously and if necessary purge bearings or clean the application area prior to application.

### DOSAGE

Do not over-lubricate and apply the quantity of grease recommended by the bearing or equipment manufacturer.

### GREASE

#### Packaging Details

Art. No.: 68770  
Content: 400 gr  
Packaging: 12x400 gr

#### Technical Specifications

Performance level DIN 51825: KP 2 N-20  
Thickener: Lithium complex  
Colour: Red / Blue  
Base Oil: Refined mineral oil  
NLGI class: 2  
Base oil visc. @ 40°C: 150 min.  
Worked penetration: 265 to 295  
Operating Temp.: -20°C to +150°C  
Water washout @ 39°C: 3  
Four Ball Weld Load: 450 kg.



## LITHIUM GREASE MP2

### PRODUCT DESCRIPTION

ARDINA Lithium Grease MP2 is a high quality multi-purpose grease which can be used for all anti-friction and plain bearings. This grease is used extensively for applications throughout the automotive and industry sectors.

### BENEFITS

- ✓ Versatile multi-purpose grease
- ✓ Good sealing properties
- ✓ Good water resistance protects components from corrosion operating in wet conditions

### USAGE

Follow the recommendations from the equipment and / or bearing manufacturer. Check compatibility with the grease applied previously and if necessary purge bearings or clean the application area prior to application.

### DOSAGE

Do not over-lubricate and apply the quantity of grease recommended by the bearing or equipment manufacturer.

### GREASE

#### Packaging Details

Art. No.: 68771  
Content: 400 gr  
Packaging: 12x400 gr

#### Technical Specifications

Performance level DIN 51825: K 2 N-20  
Thickener: Lithium soap  
Colour: Characteristic  
Base Oil: Blend mineral oils  
NLGI Class: 2  
Worked Penetration: 265 to 295  
Dropping Point: 185°C  
Operating Temp.: -20 C to +140 C  
Water washout: 5%



## LITHIUM MOLY EP2 GREASE

### PRODUCT DESCRIPTION

ARDINA Lithium Moly EP2 Grease is a premium quality multi-purpose grease which can be used in all plain bearings that are subjected to high load conditions. The incorporation of molybdenum disulphide imparts a high degree of wear protection against load, shock loading and dusty environments. This grease is used extensively for applications throughout the automotive and industry sectors.

### BENEFITS

- ✓ Excellent extreme pressure (EP) and anti-wear performance
- ✓ High degree of corrosion protection
- ✓ Remarkably versatile multi-purpose grease

### USAGE

Follow the recommendations from the equipment and / or bearing manufacturer. Check compatibility with the grease applied previously and if necessary purge bearings or clean the application area prior to application.

### DOSAGE

Do not over-lubricate and apply the quantity of grease recommended by the bearing or equipment manufacturer.

### GREASE

Art. No.:	68772	Performance level DIN 51825:	KPF 2 N-20
Content:	400 gr	Thickener:	Lithium complex
Packaging:	12x400 gr	Colour:	Grey/black
EUR Pallet:	1.176 pcs	Base Oil:	Blend mineral oils
		NLGI class:	2
		Worked Penetration:	265 to 295
		Dropping point:	185 C
		Operating temp.:	-20 C to +140 C
		Water washout @39 C:	3%
		Four ball weld load:	>315 kg
		Solids:	1%



## GASOLINE DETOX PRO

### BENEFITS

- ✓ Extremely effective concentrated problem solver for all deposit related problems in gasoline engines
- ✓ Cleans the fuel system including injectors, valves and combustion chamber
- ✓ Prevents deposit build-up in and malfunctioning of the catalytic converter
- ✓ Boosts octane number by 2 - 4 points
- ✓ Improves combustion and restores engine power
- ✓ Improves fuel economy
- ✓ Reduces toxic emission
- ✓ Eliminates rotten egg smell
- ✓ Protects against corrosion

### USAGE

All gasoline engines (including direct injection) with or without turbo or catalytic converter.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with gasoline.

### DOSAGE

One bottle treats 40 to 60 litres of gasoline.



### PREMIUM SERIES

#### Packaging Details

Art. No.:	68777
Content:	500 ml
Packaging:	12x500 ml
Pallet:	90 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,80
Flash Point:	> 61°C
Colour:	Amber / Brown
Odour:	Characteristic

## DIESEL DETOX PRO

### BENEFITS

- ✓ Extremely effective concentrated problem solver for all deposit related problems in diesel engines
- ✓ Cleans the fuel system including injectors, valves and combustion chamber
- ✓ Cleans the diesel particulate filter (DPF)
- ✓ Extends lifetime of the diesel particulate filter (DPF)
- ✓ Cleans the catalytic converter
- ✓ Keeps the turbo and EGR-valve clean
- ✓ Boosts cetane number and lubricates the fuel pump
- ✓ Restores engine power and improves fuel economy
- ✓ Reduces toxic emissions

### USAGE

For all diesel engines (incl. common rail) with or without turbochargers or diesel particulate filter.

### DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel. Drive 20 - 30 minutes preferably with elevated RPM (>3.000).

### DOSAGE

One bottle treats 40 to 60 litres of diesel fuel. Do not overdose!

### PREMIUM SERIES

#### Packaging Details

Art. No.:	68778
Content:	500 ml
Packaging:	12x500 ml
Pallet:	90 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,81
Flash Point:	> 61°C
Colour:	Brown
Odour:	Characteristic



## BORTEC FRICTION FIGHTER

### BENEFITS

- ✓ A new generation, boron ester based friction reducer and anti-oxidant, which adds unique features to any standard motor oil
- ✓ Forms a protective ceramic layer reducing friction and wear
- ✓ Boosts oil performance and delays oil-ageing
- ✓ Reduces engine noise level and vibrations
- ✓ Restores engine power and reduces fuel consumption.
- ✓ Provides long term protection of your engine
- ✓ Does not contain solid particles

### USAGE

For all gasoline, diesel and LPG engines with or without turbocharger, catalytic converter or particulate filter. Suitable for use with all commercially available engine oils including low or mid SAPS engine oils. Does not clog filters.

### DIRECTION

Add contents of one bottle to the warm motor oil. Let the engine run for a few minutes to optimize mixing. Make sure the oil contents does not exceed the maximum oil level in your engine.

### DOSAGE

One bottle treats 4 to 6 litres of motor oil.

### PREMIUM SERIES

#### Packaging Details

Art. No.:	68776
Content:	300 ml
Packaging:	24x300 ml
Pallet:	98 cartons
Languages:	EN, DE, FR, ES

#### Technical Specifications

Density g/cm <sup>3</sup> :	0,86
Flash Point:	201°C
Colour:	Yellowish
Odour:	Characteristic





[www.ardinacarcare.com](http://www.ardinacarcare.com)